

P5V - LOUDSPEAKER



Main, Surround & Height Channels

INTRODUCTION

The P5V delivers the full dynamic range experience to smaller rooms and rooms with multiple surrounds and height speakers. Its compact cabinet can be oriented either vertically or horizontally, even mounted on the ceiling, thanks to its 80 degree circular waveguide and 1" pro compression driver.

The P5V comes in semi-matte black or white finish with a magnetically attached removable grille.

TECHNICAL SPECIFICATIONS

Impedance	8 ohms nominal Phase angles less than 45 degrees	Components	Midrange 5.25" driver with 26mm voice coil in 5 litre sealed box
Power Handling Continuous Peak	75W 250W	High Frequency	1" compression driver on a circular constant directivity waveguide
Frequency Response -3dB	90Hz and 20Hz	Connectivity	Gold plated large diameter binding posts
Maximum SPL Freestanding Peak In wall Peak	107dB continuous 113dB 113dB continuous 119dB	Wall Mount	1 Inserts for VESA 100 bracket and keyholes provided for both vertical and horizontal mounting
Dispersion Pattern -6dB	Constant directivity; 80° circular from 2.5kHz	Dimensions WxHxD	18.5" x 7.5" x 4.5" 470 x 190 x 115 mm
Sensitivity 1W/1m	91dB	Shipping Carton WxHxD	23.6" x 11.6" x 7.9" 600 x 295 x 200 mm
Crossover	Asymmetrical, phase aligned 2.2kHz, BSC	Net Weight	11 Lbs / 5 Kg
Finish	White or Black semi-matte painted	Shipping Weight	13.2Lbs / 6 Kg
Recommended Amplifier	1-ch DA03-DSP	Assembly	Belgium; 100% QC testing

