

P6iW Mk2 - LOUDSPEAKER

SOUND

PROCELLA®

PERFECTED

Main, Surround & Height Channels

INTRODUCTION

From the P6V comes the P6iW Mk II which brings Procella reference quality audio and a very wide dynamic range in a shallow in-wall cabinet (only 3,9" / 100 mm). This makes it easy for integration with flatscreen, projection screens, and surround speaker environments. A 6.5" high-efficiency woofer driver combines with an pro 1" Neodymium compression driver mounted on a Procella constant directivity wave guide.

It produces uncompressed dynamics at high output levels with lifelike clarity for music and movies. Identical Voice™ timbre-matched to all other Procella speaker models.

TECHNICAL SPECIFICATIONS

Impedance	8 ohms nominal Above 10 ohms working range	Components	Midrange	6.5" driver with 40mm voice coil in 9 litre sealed box
Power Handling	Continuous Peak	High Frequency	1" neodymium driver with a polyester diaphragm on elliptical constant directivity waveguide	
Frequency Response	-3dB	Connectivity	Screw terminals	
Maximum SPL	in wall/ceiling peak	Dimensions	Speaker HxW	19.3" x 13.4" 490 x 340 mm
Dispersion Pattern	-6dB	Depth (fits EU/US walls)	Overall 4.5" / 118 mm Inside wall 3.9" / 100 mm	
Sensitivity	1W/1m	Cut out dimensions Grille HxW	18" x 12" / 455 x 305 mm 19.7" x 13.8" / 500 x 350 mm	
Crossover	Asymmetric Linkwitz-Riley 1.9kHz, BSC	Shipping Carton	WxHxD	23.6" x 15.8" x 9.8" 600 x 400 x 250 mm
Finish	White and Black grilles included	Net Weight		16.5 Lbs / 7.5 Kg
Recommended Amplifier	1-ch DA03-DSP	Shipping Weight		17.6Lbs / 8.7 Kg
		Assembly		Belgium; 100% QC testing

